

Air/O₂ Blender: Standard LOW FLOW Blender Model 2003K

2003K Standard LOW FLOW Blender w/ Bleed Control



Key features

Comes with a **DISS Oxygen Port** on the left-hand side

That allows the user to install a flow meter of their choice

A **BLEED CONTROL** knob on the Right-side

That allows the user to activate the bleed flow (3 lpm) in situations where accuracy is desired for use below 3 lpm

Additional DISS Oxygen Port on the bottom Unique feature on the right-side BLEED Control (3 lpm)

The right-side flow meter is installed on an integrated bleed control switch: When the right side is not needed, the bleed flow (3 lpm) can be disabled by pushing and rotating the flow meter forward when needed, simply return it to the upright position and use as desired

Standard input fittings are DISS for Air and Oxygen

But, NIST fittings on the blender is also available.

Air/O₂ Blender: Standard LOW FLOW Blender Model 2003K

Technical Specifications

Oxygen Concentration Range	21 to 100 %
Number of ports	2 (left side and bottom)
Flow Range Accuracy	0-3 lpm when bleed switch is on, 3-30 lpm when bleed switch is off
Accuracy	+/- 3% full scale
Bleed flow	3 lpm (when activated)

Ordering information

2003K	Low Flow blender with left side and bottom DISS port and Bleed control knob on left side
2007	Standard input fittings on the Blenders are DISS AIR and OXYGEN. If you want NIST input fittings, add this part number to the order

Dimension & Weight

Height	Width	Depth	Weight
6.64" (16.9 cm)	5.48" (13.9 cm)	4.56" (11.6 cm)	2.38 lbs. (1.08 kg)

Optional Accessories

High Pressure Hose Kit	2', 3' or 10' long
Bracket	Wall Mount, Pole Mount, Rail, headwall configuration
Quick Connect Fittings	Ohmeda, Chemtron, Quick Connect fittings

**This data is subject to change without a prior notice.*